

GENESIS™

RAPID SEAL II™ TUBE SEALER

Flexible multi-head sealer with fixed head
and handheld sealer

MODEL# SE540
CAT# 428-SE540



High-speed sealing power with proven performance.

The GENESIS™ RapidSeal II™ SE540 is a high-performance RF tube sealer engineered for fast sealing of PVC tubing in blood processing, cell therapy, and biopharmaceutical applications. It produces strong, uniform, easy-to-separate seals in seconds and provides multi-head flexibility to maximize efficiency for high volume segmenting.

Features:

- Linkable multi-head configurations
- Notched Seal™ for easy separation
- “Intelligent” RF Board – adjusts to all standard PVC blood tubing
- RAPID SEAL II™ seals in 0.5 to 1.2 seconds
- 6’ standard cable for handheld sealer
- CE and UL compliant

GENESIS™ RAPID SEAL II™ TUBE SEALER

Flexible multi-head sealer with fixed head and handheld sealer



Easy-to-remove head protector simplifies maintenance.



Adjustable link bars and thumb screws hold sealing heads firmly in position.



Handheld sealer provides operators with control and flexibility.

Precision. Reliability. Confidence.

GENESIS™ Tube Sealers provide dependable, high-performance sealing you can trust.



Multi-Head Configurations:

The SE530 Tube Sealer can be used independently or linked as a multi-head sealing unit with flexible head spacing (75 / 80 / 85 / 90 mm)



Ordering Information

Model#	SE540
CAT#	428-SE540

Specifications

Sealing Head Configuration	Fixed Sealing Head and Handheld Sealer
Dimensions	6.9"W x 6.1"H x 13"D 176mm W x 156mm H x 331mm D
Weight	11.0 lbs / 5.0 Kg
Power Type	AC
Power Source	AC 100-240V, 50/60 Hz
Max Tubing Diameter	6 mm (1/4")
Coaxial Cable	6' Standard RF Cable
Warranty	1 Year (Extended Service Agreements Available)

Included Components:

- Handheld Sealer
- 6' Coaxial Cable
- Spare Fuses (2)
- Spare Splashguards (5)
- Link Bars (2)
- Thumb Screws (4)
- Signal Cable (1)
- Two-Unit Power Cable
- AC Power Cord



Splash Guard for Genesis Hand Sealers

CAT:428-SPLGD-HS

- Provides Operator Safety
- Designed for SE340, SE540, and SE640

GENESIS BPS™